



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4313BR5752

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	EFFEBI S.p.A. Via Giuseppe Verdi 68, I-25073 Bovezzo (BS)
Distributor <i>Vertreiber</i>	EFFEBI S.p.A. Via Giuseppe Verdi 68, I-25073 Bovezzo (BS)
Product Category <i>Produktart</i>	gas fittings: Shut-off valve for local gas distribution <= PN 16 (4313)
Product Description <i>Produktbezeichnung</i>	Straight pattern ball valve optional with assembly flange according to DIN ISO 5211 for application of an electrical or pneumatic actuator
Model <i>Modell</i>	SUN WP...; ALBA....
Test Reports <i>Prüfberichte</i>	type testing: 21-00321-AB01-090 from 11.10.2021 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DIN EN 13774 (01.05.2013)

Date of Expiry / File No. 17.07.2026 / 21-0446-GNV
Ablaufdatum / Aktenzeichen

70028-04-A-DE

16.12.2021 Pz A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases according to G 260: 03.2013	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 8	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 10	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 15	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 20	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 25	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 32	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 40	
SUN WP...; ALBA....	nominal pressure rating: 16 bar (MOP 16) nominal diameter: DN 50	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
SUN WP 2551; ALBA 2601, ALBA 2611	connection: on both sides internal thread Rp 3/8 (DN8) ...Rp 2 (DN50) according to DIN EN 10226-1
SUN WP 2552; ALBA 2602; ALBA 2612	connection: at the input side internal thread Rp 3/8 (DN8) ...Rp 2 (DN50); at the outlet side external thread Rp 3/8 (DN8) ...Rp 2 (DN50), in each case according to DIN EN 10226-1
...2601; ...2602	handle: hand lever
...2611; ...2612	handle: butterfly handle
...2551; ...2552	handle: hand lever as well as electrical or pneumatic actuator

certified Components**zertifizierte Bauteile / Werkstoffe**

Registr. No. <i>Registrier-Nr.</i>	Component <i>Bauteil (Produktart)</i>	Model/Type <i>Modell/Typ</i>	Manufacturer <i>Hersteller</i>
DG-5112CQ0195	Elastomer material for seals in gas appliances	01/T70 FKM/01/T70 FKM	LAV.EL GOMMA S.r.l.

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

ambient temperature range: -20...+60 °C